

D&L Engineering Solutions

9D Lavendergate Dr. Southgate Business Park,
Umbogintwini, 4120, South Africa
Tel: +27 31 914 0027
Email: admin@dlengineering.co.za



CASINGA SAFETY PRODUCTS

PART #	ITEM	PRODUCT IMAGE	DETAILS	QTY Required
BO160	BOLLARD		PIPE DIAMETER: 160 mm PROTECTION LEVEL: Forklift 3 tons, 4.5 km/h STANDARD HEIGHT: 800 mm (customizable 500-1200 mm)	
BO130	BOLLARD		PIPE DIAMETER: 130mm PROTECTION LEVEL: Forklift 1.5 tons, 3 km/h STANDARD HEIGHT: 800 mm (customizable 500-1200 mm)	
BO160S	BOLLARD		PIPE DIAMETER: 160mm PROTECTION LEVEL: Forklift 4 tons, 5 km/h STANDARD HEIGHT: 800 mm (customizable 500-1200 mm) PRODUCT FEATURES: High strength elastic inner core	
MB100E	MONORAIL BARRIER		PIPE DIAMETER: Cross beam 100 & column 130 mm STANDARD LENGTH: 1800 mm (centreline spacing) COLUMN HEIGHT: 450 mm PROTECTION LEVEL: Forklift 5 tons, 3 km/h	
DB100E	DOUBLE BARRIER		PIPE DIAMETER: Cross beam 100 & column 130 mm STANDARD LENGTH: 1800 mm (centreline spacing) COLUMN HEIGHT: 800 mm PROTECTION LEVEL: Forklift 5 t, 3 km/h	
PB100E	PEDESTRIAN BARRIER		PIPE DIAMETER: Cross beam 100 & column 130 mm STANDARD LENGTH: 1800 mm (centreline spacing) COLUMN HEIGHT: 1175 mm PROTECTION LEVEL: Forklift 5 t, 3 km/h	
MB160	MONORAIL BARRIER		PIPE DIAMETER: Cross beam & column 160 mm STANDARD LENGTH: 2000 mm (centreline spacing) COLUMN HEIGHT: 450 mm PROTECTION LEVEL: Forklift 5 t, 4 km/h	
DB160	DOUBLE BARRIER		PIPE DIAMETER: Cross beam & column 160 mm STANDARD LENGTH: 2000 mm (centreline spacing) COLUMN HEIGHT: 800 mm PROTECTION LEVEL: Forklift 5 tons, 5 km/h	
CB1-100	COLUMN BARRIER		PIPE DIAMETER: Cross beam 100 & column 130 mm STANDARD LENGTH: 1000 mm (centreline spacing) COLUMN HEIGHT: 450 mm PROTECTION LEVEL: Forklift 1.5t, 3 km/h	
CB2-100	COLUMN BARRIER		PIPE DIAMETER: Cross beam 100 & column 130 mm STANDARD LENGTH: 1000 mm (centreline spacing) COLUMN HEIGHT: 800 mm PROTECTION LEVEL: Forklift 3 t, 3 km/h	

CB3-100	COLUMN BARRIER		PIPE DIAMETER: Cross beam 100 & column 130 mm STANDARD LENGTH: 1000 mm (centreline spacing) COLUMN HEIGHT: 1175 mm PROTECTION LEVEL: Forklift 3 t, 3 km/h	
FB-180	FORK BARRIER		STANDARD LENGTH: 2000 mm PIPE WALL THICKNESS: 13 mm PROTECTION LEVEL: Forklift 4.7 tons, 5 km/h DIMENSIONS: height 180 mm, width 124 mm	
RP400	RACK BARRIER		PRODUCT HEIGHT: 400 mm COMPONENT HEIGHT: 100 mm PROTECTION LEVEL: 3 tons, 3.5 km/h NOTE: 4 units make up a set	
DF1-160	HEIGHT RESTRICTOR		PIPE DIAMETER: 160 mm COLUMN HEIGHT: 4500 mm STANDARD LENGTH: 5200 mm (centreline spacing) PROTECTION LEVEL: 3 tons, 3 km/h	
SD1-100II	SAFETY DOOR		PIPE DIAMETER: Cross beam 100 & column 130 mm DOOR WIDTH: 1700 mm COLUMN HEIGHT: 1175 mm	
SD2-130	SAFETY DOOR		CROSS BEAM DIAMETER: 63 & 100 mm DOOR WIDTH: 1000 mm COLUMN DIAMETER: 130 mm COLUMN HEIGHT: 1175 mm	
AB-01	ALARM BAR		PIPE DIAMETER: 130 mm STANDARD LENGTH: 2000 mm PRODUCT COMPOSITION: two light strips+sensors PRODUCT PERFORMANCE: ① When tilt is $\geq 15^\circ$ or the vibration is $\geq 10\text{mm/s}$, it will activate an audible and visual alarm (within one minute, it will beep 20 times, flash 30 times) ② Collision limit: 5t ③ Tensile limit: 300kg	
PB-01	PLATFORM BUMPER		PIPE DIAMETER: 160 mm PRODUCT COMPOSITION: 2 pieces, 8 anti-collision tubes in total PROTECTION LEVEL: 20 tons, 0.6 km/h	

NOTE:

All floor mounted products include fixing bolts
Installation options are available on request.